



## CAMERA CCTV 360° DAY/NIGHT 560TVL OPTICAL ZOOM 36X GGM ANP36X



ACCESSORIES (WALL MOUNT  
BRACKET NOT INCLUDED)

560 TVL

Optical zoom 36x

WDR function

24 privacy masks

IP67

The **GGM ANP36X** is a high level speed dome CCTV camera with a powerful optical zoom 36x. The sharp images, high reliability and flexible mounting options make the **GGM ANP36X** a camera ideally suited for retail stores, schools, industrial and public sites and locations where monitoring and surveillance is essential. All in all a cost-effective solution, that is easy to install and even easier to operate.

The **GGM ANP36X** provides IP67-rated protection against dust and water and vandal proof. The built-in heaters, fans ensure that the camera can be used in varying weather conditions and temperatures ranging from -40 °C to + 60°

### MAIN FEATURES

- Optical zoom 36X
- Horizontal Resolution : 560TVL
- Sensibility : up to 0,0005 Lux
- IP67
- WDR function
- 24 privacy masks
- 4 pattern tours memorizing



GGM ANBRAS



GGM ANBRASBOX



## PRODUCT SPECIFICATION

VIDEO		PAN / TILT / ZOOM		MISCELLANEOUS	
Video Format	PAL	Picture effect	Flip mirror effects	Alarm	6 inputs / 1 output
Optical zoom	36x	P/T Operation	Pan 360° continuous, Tilt 92°	Preset titles	Up to 20 characters
View angle	57.8° ~ 1.7°	Manual Pan speed	0.1°/s~90°/s	Password protection	Alphanumeric dome OSD setup protection
Minimum working distance	320 mm wide 1500 mm tele		0.1°/s max digital zoom 0.4°/s max optical zoom. Turbo mode 150°/s	Operating temperature	-40°C~+60°C
Effective pixels	Up to 440 000 pixels	Manual tilt speed	0.1°/s~45°/s	Operating humidity	20~80% RH
Video output	1x BNC 1Vpp 75 Ohm		0.1°/s max digital zoom 0.4°/s max optical zoom	Storage temperature	-20°C~60°C
Horizontal resolution	560 TVL	Preset speed	Pan : 430°/s	Dimensions	216,6mm x 324mm (diam x H)
S/N ratio	More than 50dB		Tilt : 200°/s	Weight	3.8Kg
		Proportional P/T	Provided	Power supply	AC 24V +/- 10%
		Pan Tilt limit	Defined by user	Consumption max	46W
		Auto Flip	Yes	Language	English, French
		Zoom limit	36X, digital 72X, 144X, 288X, 432X	Vandal proof	750 Kg impact resistance
		Preset points	Up to 256	Protection	IP67
		Programmable tours	4 pattern tour memorizing up to 6 minutes of manual control	Built in	Heater and blower
		Privacy zone	Up to 24 zones (3D privacy zone)		
		Scan function	Random, frame, auto scan selectable		
PICTURE		CONTROL		WARRANTY	
Sensor	1/4" SONY Exview HAD CCD	Interface	Support absolute (X, Y, Z) position		2 years
Minimum illumination	Normal Mode : 0.07 Lux (F1.6 1/60 1/50 sec ICR OFF 10 IRE) Slow shutter mode : 0.005 Lux (F1.6 1/4 1/3 sec ICR OFF 10 IRE) Night mode : 0.0075 Lux (F1.6 1/60 1/50 sec ICR ON 10 IRE) Slow shutter mode : 0.0005 Lux (F1.6 1/4 1/3 sec ICR ON 10 IRE)	Baud rate	RS 485 2400, 4800, 9600, 19200 bits/s (DIP-sw selectable)		
Focus	Auto (sensitivity normal, low) One push-AF, Manual, Infinity, Interval AF, Zoom trigger AF				
Gain control	Auto/manual (-3 ~ 28dB, step 2dB) White balance Alarm function Day/Night mode Wide Dynamic 128X Motion detection				
				ACCESSORIES	
				GGM ANBRAS	Simple wall mount bracket support up to 10 Kg
				GGM ANBRASBOX	Wall mount bracket with junction box support up to 10 Kg

